

Canopia Sedum Mat

Vegetated sedum mat for green roof applications.

INTENDED USE

The Canopia Sedum Mat is to be used in conjunction with the other relevant and specified components of the BMI Extensive Green Roof System.

It can be used on flat, (with min design fall of 1:40) and sloping roofs, (upto a maximum pitch of 40 degrees), with the appropriate accompanying anti-slip products.

INSTALLATION

Level growing medium thoroughly before laying the mats.

Lay mats manually, with a minimum of 2 persons per mat required. Discard any dry, damaged, frosty or waterlogged mats.

Lay mats diagonally or perpendicular to the roof slope. Butt joints together to prevent gaps. Do not stretch mats. As laying proceeds, firm the mats to ensure full contact with the growing medium. Do not use rollers.

Finish edges using whole mats. Brush in substrate to fill joints. Water thoroughly, immediately after laying and dressing until the entire build-up is water saturated (30 litres/m²). Continue watering 2-3 times with 30 litres/m², to keep moist until fully rooted in.

STORAGE

Mats should be installed on the day of delivery. Any mats that cannot be installed on the day of delivery must be rolled out and watered immediately afterwards and kept moist. Rolled out vegetation mats can be stored for 1 - 2 weeks if kept moist.

TECHNICAL SERVICES

For further information and technical support, please contact our technical services team:

T: +44 (0) 330 123 4585

E: technical.uk@bmigroup.com



PRODUCT DATA

Product Code	20000816
Vegetation	Mixed sedum species*
Thickness	Approx. 15 - 25 mm (excluding vegetation)
Weight	Approx. 20 - 25 kg/m ²
Standard Roll Size	2.0m x 1.0m (2.0m ² /mat)
Delivery form	Rolled, on pallets with approx. 40m ² per pallet

* May contain a small amount of naturally seeded herbs and grasses.

BMI Group UK Limited

BMI House, 2 Pitfield, Kiln Farm, Milton Keynes, MK11 3LW
bmigroup.com/uk

Product, technical standards and codes of practice are under constant review. We reserve the right to change and amend products and information without prior notice. For the latest information, suitability and specification advice, please contact BMI Icopal technical services team.