

Sealoflex Prima

2-Part Primer

Sealoflex Prima 2-Part Primer is a solvent-free, two component primer with a polyurethane base. It is a component of the Sealoflex Prima System.

INTENDED USE

Sealoflex Prima 2-Part Primer is used to prepare the majority of roof substrates including asphalt and bitumen and PVC membranes; and to enhance the adhesion of Sealoflex Prima Waterproof Coating.

INSTALLATION SUMMARY

Before applying Prima 2-Part Primer ensure that the surface is clean, dry and sound.

Prima 2-Part Primer is a two component liquid that requires mixing before application.

Do not apply if rain is imminent.

For detailed application instructions and surface preparation, refer to the Sealoflex Prima Installation Manual or contact BMI Icopal Technical Services Team for further advice.

CLEANING

Clean tools immediately after use using Sealoflex MEK Cleaner. Wash hands thoroughly after use.

TYPICAL SPECIFICATION

Primer to be BMI Sealoflex Prima 2-Part Primer, as supplied by BMI UK & Ireland. Primer to be applied at an approximate rate of 0.3kg/m² depending on the porosity of the substrate.

PRODUCT DATA

Container size	5kg (2 x 2.5kg sachets)
Form	Liquid
Application rate	0.3kg/m ²
Coverage per pack	Approx. 16 m ²
Workability period	25 minutes*
Rainproof	Approx. 3 hours*
Walkable	Approx. 12 hours*
Overcoating period	Approx. 2 hours*
Shelf life	12 months
Colours	Cream (Component A) Dark Brown (Component B)

* Dependent on environmental conditions. Values attained at 23 °C and 50% relative humidity. Times given are reduced with higher (and increased with lower) surrounding and work surface temperatures.

CERTIFICATION

BMI Sealoflex Prima has been independently site and laboratory tested by the British Board of Agrément and awarded BBA certificate number 13/5028.



SAFETY, QUALITY AND ENVIRONMENT

BMI Sealoflex products are manufactured under a Quality Management System approved to ISO 9001: 2015 and an Environmental Management System approved to ISO 14001: 2015, by TÜV NORD CERT GmbH.



ISO 9001:2015
44 100 21410102



ISO 14001:2015
44 100 21410102

Information regarding transportation, handling, storage and disposal can be found on the relevant Safety Data Sheet. Health and safety information supplied by BMI Icopal must be observed. Do not allow into the sewer system or ground.

STORAGE

Containers should be stored in a dry and cool environment on a flat, level, and clean surface away from sources of ignition, including pilot lights and sparks.

Protect the product against moisture, direct sunlight and extremes of temperature. Keep containers tightly closed when not in use. In original unopened containers the shelf life is 12 months.

DISPOSAL

Components A + B (Liquid)	EWC	08 04 09
Components A + B (Cured)	EWC	08 04 10

TECHNICAL SERVICES

For further information and technical support, please contact our technical services team:

T: +44 (0) 330 123 4585

E: technical.uk@bmigroup.com



BMI Group UK Limited

BMI House, 2 Pitfield, Kiln Farm, Milton Keynes, MK11 3LW
bmigroup.com/uk

Product, technical standards and codes of practice are under constant review. We reserve the right to change and amend products and information without prior notice. For the latest information, suitability and specification advice, please contact BMI Icopal technical services team.