

Declaration of Performance



ETAG 005

19

0536

ETA 19/0536 of 08/01/2020

In accordance with Regulation (EU) N° 305/2011;

1.	Unique identification code of the product-type	BMI SEALOFLEX ULTIMA
2.	Type, batch or serial number allowing identification of the construction product as required pursuant to Article 11 (4)	Batch Number - See packaging of the product
3.	Intended use	Liquid applied roof waterproofing to be used for the waterproofing of roof surfaces against penetration of atmospheric water.
4.	Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5)	BMI Group Management UK Ltd 20 Air Street 5th Floor London W1B 5 AN England
5.	Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2)	Not relevant
6.	System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, or Annex V	System 3
7.	In case of the declaration of performance concerning a Construction product covered by a harmonised standard	Not relevant
8.	In case of the declaration of performance concerning a Construction product for which a European Technical Assessment has been issued	The approval body <i>Centre Scientifique et Technique du Bâtiment</i> (CSTB) No. 0679, issued ETA 19/0536 of 08/01/2020 on the basis of ETAG 005, part 6.

Declaration of Performance

9. Declared Performance

ESSENTIAL CHARACTERISTIC	PERFORMANCE	Harmonised technical specification
Working life	W3	ETAG 005, Part 6 (edition 2004) ETA 19/0536 of 08/01/2020
Climatic Zones	M & S	
Imposed loads	P4 non compressive substrate	
	P2 compressive substrate	
Roof slope	S1 to S4	
Lowest surface temperature	TL4 (-30°C)	
Highest surface temperature	TH4 (+90°C)	
External fire performance	Brof (t1), Broof (t4)	
Reaction to fire	Class E	
Water vapour diffusion resistance factor	$\mu \approx 1780$	
Resistance to wind loads	≥ 50 kPa on concrete substrate	
Statement on dangerous substances	None	
Resistance to plant roots	Resistant to Plant Roots	
Resistance to slipperiness	NPA	
	NPA (No Performance assessed)	

10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Stéphanie Camerlynck, PhD
Position: Technology Manager Liquid Applied Waterproofing
Place: Paris, FRANCE / Date: 20th January 2020

