

Declaration of Performance



ETAG 005

19

0766

ETA 19/0766 of 18/02/2020

In accordance with Regulation (EU) N° 305/2011;

| | | |
|----|--|---|
| 1. | Unique identification code of the product-type | BMI SEALOFLEX ENDURA |
| 2. | Type, batch or serial number allowing identification of the construction product as required pursuant to Article 11 (4) | Batch Number - See packaging of the product |
| 3. | Intended use | Liquid applied roof waterproofing to be used for the waterproofing of roof surfaces against penetration of atmospheric water. |
| 4. | Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11 (5) | BMI Group Management UK Ltd 20 Air Street 5th Floor London W1B 5 AN England |
| 5. | Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12 (2) | Not relevant |
| 6. | System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, or Annex V | System 3 |
| 7. | In case of the declaration of performance concerning a Construction product covered by a harmonised standard | Not relevant |
| 8. | In case of the declaration of performance concerning a Construction product for which a European Technical Assessment has been issued | The approval body <i>DiBt</i> , issued ETA 19/0677 of 18/02/2020 on the basis of ETAG 005, part 4. |

Declaration of Performance

9. Declared Performance

| ESSENTIAL CHARACTERISTIC | PERFORMANCE | Harmonised technical specification |
|--|--|---|
| Working life | W3 | ETAG 005, Part 4 (edition 2004) ETA 19/0766 of 18/02/2020 |
| Climatic Zones | M & S | |
| Imposed loads | P1 to P4 | |
| Roof slope | S1 to S4 | |
| Lowest surface temperature | TL4 (-30°C) | |
| Highest surface temperature | TH4 (+90°C) | |
| External fire performance | Broof (t1), Broof (t2), Broof (t3) and Broof (t4) | |
| Reaction to fire | Class E | |
| Water vapour diffusion resistance factor | $\mu \approx 10\,000$ | |
| Resistance to wind loads | ≥ 50 kPa on concrete substrate | |
| Statement on dangerous substances | None | |
| Resistance to plant roots | NPA | |
| Resistance to slipperiness | NPA | |
| | NPA (No Performance assessed) | |

10. Declaration

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.
This declaration of performance (DoP) is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Stéphanie Camerlynck, PhD
Position: Technology Manager Liquid Applied Waterproofing
Place: Paris, FRANCE / Date: 24th June 2020

