

Canopia Protection Fleece 300

Canopia Protection Fleece 300 is mixed fibre fleece material used as a separation and protection layer to reduce any point loadings on the waterproofing membrane that sits below it.

INTENDED USE

Used as a protective layer on waterproofing with an additional separating and water reservoir function. Provides separation of products made from incompatible materials (e.g. PVC and bitumen).

INSTALLATION SUMMARY

Handle with care to avoid any damage.

When required, the Canopia Protection Fleece is rolled out and cut to shape, ensuring that drainage outlets are not covered. The Canopia Protection Fleece should be overlapped by at least 150mm on top, bottom and sides.

Be careful to NOT damage the waterproofing membrane when making any cuts, and we advise the use of a protection board to prevent this.

STORAGE

The product must be kept dry and clean and protected from UV light prior to use.

TECHNICAL SERVICES

For further information and technical support, please contact our technical services team:

T: +44 (0) 330 123 4585

E: technical.uk@bmigroup.com



PRODUCT DATA

Product Code:	20000814
Material	PP / PES / acrylic recycled fibres
Nominal thickness	Approx. 3.6 mm
Material Weight	Approx. 300 g/m ²
Colour	Multicolour with print
Water reservoir	Approx. 2 L/m ²
Delivery weight	Approx. 30 kg per roll, 205 kg per euro pallet
Pack size	0.45 m dia. x 2.0 m height per roll
Quantity / delivered unit	100 m ² per roll (2 m x 50 m) 600 m ² per euro pallet
Delivery form	6 rolls per euro pallet (0.8 m x 1.2 m)
Storage	Dry and protected from UV
Rotproof	Yes



BMI Group UK Limited

BMI House, 2 Pitfield, Kiln Farm, Milton Keynes, MK11 3LW
bmigroup.com/uk

Product, technical standards and codes of practice are under constant review. We reserve the right to change and amend products and information without prior notice. For the latest information, suitability and specification advice, please contact BMI Icopal technical services team.